



VP-728

9-Input ProScale™ Presentation
Scaler/Switcher

| HDMI | HDCP Compliant



The VP-728 is a 9-input scaler/switcher for analog and digital video, unbalanced stereo, and S/PDIF audio signals. It up- or down-scales any video signal: composite, s-Video (Y/C), component video (YUV), HDMI, computer graphics video and JPEG files to a selectable graphics or HDTV output resolution via identical HDMI or 15-pin HD outputs. It provides glitch-free switching between sources through FTB™ (fade-thru-black) switching technology

FEATURES

HQV® Video Processing

Fade-Thru-Black (FTB™) Switching - The video fades to black and then the new input fades from black for smooth, glitch-free switching. The output signal provides constant sync so the display never glitches

K-IIT XL™ Picture-in-Picture Image Insertion Technology - Ultra stable picture-in-picture, picture-and-picture, and split screen capability. Any video source can be inserted into or positioned next to a computer graphics video source or vice versa with window positioning and sizing controls

Projector Anywhere™ Technology - Horizontal & vertical geometry controls to compensate for off-axis projector placement

HDTV Compatible

HDCP Compliant - The HDCP (High Definition Content Protection) license agreement allows copy-protected data on the HDMI input to pass only to the HDMI output

Video Inputs - 4 universal video (composite, s-Video, component) each on 3 RCAs, 2 computer graphics video (15-pin HD), 2 HDMI and 1 USB (for JPEG data)

Multi-Standard - Auto, NTSC (3.58/4.43), PAL (M/N/60) & SECAM

HDTV Compatible Component Input

Scaled Video Outputs - HDMI & 15-pin HD

HDTV Output Resolutions - 720p, 1080i, and 1080p

Computer Graphics Output Resolutions - 32 plus a user definable custom output resolution with selectable refresh rates

Multiple Aspect Ratio Selections - 4x3 or 16x9, anamorphic, letterbox, and user definable settings

Companion AFV (Audio-Follow-Video) - For every analog video input; supports embedded audio on the 2 HDMI inputs and outputs

Audio Inputs - 4 stereo audio or S/PDIF on 2 RCA connectors for each of the 4 universal video inputs; 2 unbalanced stereo audio on 3.5mm mini jacks for each of the 2 computer graphics video inputs. Each has level adjustment

Audio Outputs - S/PDIF and stereo audio (RCAs). Transcodes stereo or S/PDIF audio to both stereo and S/PDIF audio. Embeds & de-embeds HDMI audio. Master volume control

Audio Delay - Adjustable from 0 to 340msec

Built-in Time Base Corrector - Stabilizes unstable video sources

Built-in ProcAmp - Color, hue, sharpness, contrast, and brightness are set individually for each input

Text Overlay

Front Panel Lockout

Front Panel Freeze Frame

Video Blanking - Blue or black screen selectable

Zoom - 100% to 400%

Flexible Control Options - Front panel, IR remote (with on-screen menus) & RS-232

Worldwide Power Supply - 100-240V AC



KRAMER

TECHNICAL SPECIFICATIONS

INPUTS: 4 universal Y/CV, Pb/C, Pr (composite, s-Video and component) 1 Vpp/75Ω on RCA connectors;
2 UXGA on a 15-pin HD connector (VGA through UXGA);
2 HDMI connectors;
1 USB connector;
For each universal input there is a corresponding (unbalanced) audio stereo input (1V nom./25kΩ minimum) and digital stereo S/PDIF input (32kHz to 96kHz sample frequency/75Ω) on RCA connectors;
For each UXGA input there is a corresponding (unbalanced) audio stereo input on a 3.5mm mini jack connector

OUTPUTS: 1 HDMI connector;
1 UXGA format on a 15-pin HD connector;
1 unbalanced audio stereo output (1V nom./50Ω) on RCA connectors;
1 digital stereo S/PDIF output (32kHz to 96kHz sample frequency/75Ω) on an RCA connector

COMPLIANCE WITH HDMI STANDARD: Supports HDMI and HDCP

OUTPUT RESOLUTION: Native HDMI, 640x480x60Hz, 640x480x75Hz, 800x600x50Hz, 800x600x60Hz, 800x600x75Hz, 1024x768x50Hz, 1024x768x60Hz, 1024x768x75Hz, 1280x768x50Hz, 1280x768x60Hz, 1280x720x60Hz, 1280x800x60Hz, 1280x1024x50Hz, 1280x1024x60Hz, 1280x1024x75Hz, 1366x768x50Hz, 1366x768x60Hz, 1400x1050x50Hz, 1400x1050x60Hz, 1600x1200x50Hz, 1600x1200x60Hz, 1680x1050x60Hz, 1920x1080x60Hz, 1920x1200x60Hz, 480px60Hz, 576px60Hz, 720px50Hz, 720px60Hz, 1080ix50Hz, 1080ix60Hz, 1080px50Hz, 1080px60Hz, 720x480x59.94Hz, 1280x720x59.94Hz, 1920x1080ix59.94Hz, 1920x1080x23.98Hz, 1920x1080x29.97Hz, 1920x1080x59.94Hz or custom

CONTROL: Front panel buttons/OSD, IR remote control, RS-232 on a 9-pin D-sub connector

ADDITIONAL CONTROLS: Picture-In-Picture: Video-in-Graphics (or vice versa), Picture-and-Picture or Split Screen (two images side-by-side), freeze, zoom, different selectable vertical refresh rates, video and audio ProcAmp control, output image scaling and aspect ratio change, EDID capture, text overlay, slide show

POWER CONSUMPTION: 100-240V AC, 50/60Hz, 30VA automatic power supply

INCLUDED ACCESSORIES: Null-modem adapter, rack "ears", IR remote control, 2 sets of C-SF/2RVM-0.5 cables, power cord, control application program via RS-232 (PC) and via Ethernet (i-Phone® and PC)

PRODUCT DIMENSION: 19" x 9.34 x 1U (43.6cm x 23.72cm 4.36cm) W, D, H

PRODUCT WEIGHT: 2.2kg (4.8lbs) approx

SHIPPING DIMENSION: 52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H

SHIPPING WEIGHT: 3.3kg (7.2lbs) approx

