



## DK42P-3

HighSecLabs Secure Dual Head 4-Port 4K30  
UHD DisplayPort KVM Switch

| HDMI | C-KVM



DK42P-3 is a secure dual head 4-port, 4K30 UHD DisplayPort KVM switch. It enables users to share peripherals – keyboard, video, mouse and audio – between four different security-level networks/computers while isolating all hosts and protecting against data leakage and malicious attacks through shared peripherals. DK42P-3 provides the highest possible isolation between connected computers and is NIAP Common Criteria Protection Profile version 3.0 (PP3.0) certified

### FEATURES

**Highest Security by Design** - NIAP Common Criteria Protection Profile version 3.0 (PP3.0) certification for peripheral Sharing Switch (PSS) devices

**4K30 UHD Resolution** - Supports resolutions up to 3840×2160 @30Hz

**Work Freely Without Compromising Security** - Display and control classified and non-classified computers without compromising security

**Prevent Information Leaks** - Block peripheral exploits, information leaks, eavesdropping, signal transmission, computer malware, hardware and firmware tampering

**Dual Display** - Provides flexible presentation options with duplicate or extend view modes

**Smooth Switching Between Computers (Virtual Display Technology)** - Automatically switch all peripheral control from one computer to another by dragging the cursor between each computer's display border

**Keyboard Lock Indication** - Caps Lock, Num Lock, and Scroll Lock indication on front panel

**Versatile and Flexible** - Configurable as a KVM switch (default) for sharing a display, keyboard and mouse between connected computers, or KM switch for sharing keyboard and mouse and simultaneously working on multiple computers connected to separate displays



# KRAMER

## TECHNICAL SPECIFICATIONS

---

**CONSOLE PORTS:** 2 HDMI connectors, 2 USB-A connectors for keyboard and mouse, 2 DIN-5 connectors for PS/2 keyboard and mouse, 1 3.5mm mini jack for unbalanced stereo audio, 1 RJ45 connector for control (RDC)

**COMPUTER PORTS:** 8 DisplayPort 1.2 connectors, 4 USB-B connectors for keyboard and mouse, 4 3.5mm mini jacks for unbalanced stereo audio

**MAX RESOLUTION:** 4K30 UHD (3840X2160 @30Hz)

**WARRANTY:** 3 years

**POWER REQUIREMENTS:** 35W max

**AC INPUT:** 100 to 240V AC

**POWER TYPE:** Internal

**OPERATING TEMPERATURE:** 32° to 104°F (0° to 40°C)

**STORAGE TEMPERATURE:** -4° to 140°F (-20° to 60°C)

**HUMIDITY:** 0-80% RH, non-condensing

**SUPPORTED OS:** Windows, Linux, Mac

**SECURITY CERTIFICATION:** NIAP Common Criteria PP3.0 for Peripheral Sharing Switch (PSS) devices

**PRODUCT CERTIFICATION:** CE, RCM, FCC class B, VCCI, TUV US, TUV Canada

**PRODUCT LIFE-CYCLE:** 10 years

**Product Dimensions** 34.20cm x 0.00cm x 5.70cm (13.46" x 0.00" x 2.24" ) W, D, H

**Product Weight** 2.0kg (4.3lbs) approx

**Shipping Dimensions** 42.00cm x 25.00cm x 8.50cm (16.54" x 9.84" x 3.35" ) W, D, H

**Shipping Weight** 2.6kg (5.6lbs) approx

