



KRAMER

Kramer KronoMeet

Cloud-Based Room Scheduling and Meeting Management Platform



Kramer KronoMeet is an enterprise class, user-friendly, cloud-based, room scheduling and management platform for Kramer KronoMeet touch panels. It streamlines and automates the management side of room bookings and provides live notifications to meeting participants. Kramer KronoMeet is designed to work seamlessly with Kramer management software and Kramer AV products enabling you to sync your room management with your AV management and deployment

FEATURES

Enterprise Class Comprehensive Room Scheduling, and Management - Empower your staff and guests with intuitive room scheduling, live on-site and remote notifications, and easy meeting search for employees and guests. Kramer KronoMeet is fully integrated with widely used scheduling platforms, including Google Calendar, Microsoft Office 365, and Microsoft Exchange

Fully Customizable and Scalable - Kramer KronoMeet is scalable to your needs, from a small business with a few meeting rooms to a large corporation

On-Screen Information Inside the Meeting Room - Integration with VIA collaboration devices enables automatic reminders on the main display when the meeting is nearly over and another meeting will be starting

Convenient Scheduling Displays - Display meeting schedules on Kramer KronoMeet touch panels at the entrance to each room

Superior User Experience - IPS 1280x800 hi-resolution screen with $\pm 80^\circ$ horizontal and vertical wide viewing angles, built-in lighting sensor for auto-adaptable brightness, with advanced 10 multi-touch points and 2-finger gesture capabilities

Secured Operation - Highly secured operation of applications such as password protected exit, hidden control buttons and so on

Secured Deployment - Flexible locking options to prevent unwanted panel-mount removal, elegantly designed to remain out of site



TECHNICAL SPECIFICATIONS

KT-107SC

PORTS

- 1 1000/100/10BaseT Ethernet: On an RJ-45 connector
- 1 DC power supply: On a 2-pin terminal block
- 1 USB: On a micro USB 2.0 connector (tabletop mount only)

GENERAL

- CPU Performance: 1.6GHz Quad Core, GPU, 2GB RAM, 16GB flash
- OS Software: Android 6.0.1
- Multi Touch: 10 points, 2-finger gesture
- Display: 7" IPS, 1280x800 RGB pixels, 16:10 aspect ratio, $\pm 85^\circ$ horizontal/vertical viewing angles, 400cd/m2 brightness, 800:1 contrast ratio
- Ethernet Port: 10/100/1000Mbps PoE LAN
- Wireless Communication: Wi-Fi 802.11 b/g/n/ac, Bluetooth 4.0

AUDIO

- Speakers: 2x1W, 8 Ω
- Microphone: -42dB ± 3 dB @1kHz sensitivity

VIDEO

- Decoding Format: HEVC/H.265, H.264, H.263, MPEG-1/2/4, VC-1, VP6/8, RV8/9/10, AVS, MVC, Sorenson Spark, M-JPEG
- Encoding Format: H.264, MVC, VP8, M-JPEG
- Camera: Front, 2M pixels, HD 720p

POWER

- Battery: Rechargeable, supports up to 3 hours of Wi-Fi operation
- Power over Ethernet: Complies with IEEE802.3af and IEEE802.3at PoE standards
- Consumption: 5V DC, 3A

USER INTERFACE

- Controls: Hidden Reset, power (ON/OFF), volume buttons
- Indicators: Touch panel status LED: flashes green during charging, steady green for fully charged, red for camera on

PHYSICAL

- Case: Black body and cover
- Mounting Options: Table top (with docking station), on-wall (with mount unit and panel mount plate)

ACCESSORIES

- Included: Power supply unit adapter (5V, 4.0A AC/DC), tabletop mount, on-wall mount unit, panel-mount plate, right-angle OTG USB cable, installation screws

MEASUREMENTS

- Product Dimension: 17.80cm x 13.00cm x 1.30cm (7.01" x 5.12" x 0.51") W, D, H
- Product Weight: 0.4kg (0.9lbs) approx.
- Shipping Dimension: 35.00cm x 21.00cm x 7.00cm (13.78" x 8.27" x 2.76") W, D, H
- Shipping Weight: 1.2kg (2.5lbs) approx

KT-1010SC

PORTS

- 1 Ethernet: On an RJ-45 connector
- 1 SD card: On an SD card (SDHC Class10 compatible) slot
- 1 USB: On a USB 2.0 type A connector
- 1 USB: On a micro USB 2.0 connector
- 1 Headphone: On a 3.5mm mini jack connector

GENERAL

- CPU Performance: GCortex-A17, quad core, up to 1.8 GHz
- GPU: Mali-T764, with TE, ASTC, AFBC technology
- System Memory: 2GB DDR3 SDRAM
- Internal Storage Memory: 8GB eMMC
- External Storage Memory: SD card (SDHC Class10 compatible)
- Touch Panel Type: 10 point capacitive multi-touch type
- Wireless Communication : IEEE 802.11 a/b/g/n/ac, Bluetooth: BT4.2
- Ethernet: 10/100/1000 Mbps LAN

AUDIO
Speaker unit: 2W+2W

VIDEO
Supported Formats: MKV, TS, FLV, AVI, VOB, MPG, DAT, ASF, RM, MOV, 3GP, MP4, WMV
Camera: 2M pixels (optional)
Supported Formats: MP2, WMA, WAV, AAC, OGG, ASF

POWER
Source: 12V/2A DC adapter
POE: Power over Ethernet (optional)

USER INTERFACE
Controls: Volume, menu, and power buttons
Indicators: LED sidebars to indicate room status

PHYSICAL
Display: TFT LCD, 10.1" (16:9 diagonal), 1280 RGB (H) x 800(V) pixels
Back-light: LED Side-light type
VESA Mounting Ready: Metal-fittings mounting screw holes for 75x75mm VESA mount

INCLUDED ACCESSORIES
12V AC/DC power adapter, on-wall mounting bracket, installation screws, 2 LED side bars, panel mounting bracket

MEASUREMENTS
Product Dimension: 25.21cm x 18.00cm x 3.00cm (9.93" x 7.09" x 1.18") W, D, H
Product Weight: 0.6kg (1.3lbs) approx.
Shipping Dimension: 49.70cm x 20.50cm x 5.20cm (19.57" x 8.07" x 2.05") W, D, H
Shipping Weight: 1.6kg (3.4lbs) approx

ENVIRONMENTAL
CONDITIONS

Operating Temperature: 0° to +40°C (32° to 104°F)
Storage Temperature: -10° to +55°C (14° to 131°F)
Humidity: 10% to 90%, RHL non-condensing



KRAMER

CONFIGURATIONS

KT-107SC	7-Inch, wall mount, dedicated touch panel for Kramer KronoMeet – application with 1 year license pre-installed
KRONOMEET-SW-EXT-1Y	Kramer KronoMeet cloud based application - 1 year license
KRONOMEET-SW-EXT-2Y	Kramer KronoMeet cloud based application - 2 year license
KRONOMEET-SW-EXT-4Y	Kramer KronoMeet cloud based application - 4 year license