



## PSE-1

Single 10G HDBaseT & Ethernet Power  
Injector

| HDBaseT



The PSE-1 provides power remotely over Ethernet to any device capable of acting as a PoE acceptor (for example, a wallplate, where it may be difficult to connect an external power supply). This allows a single HDBT LAN cable to provide both data and electrical power to compatible devices

## FEATURES

**Total Range** - Up to 100m (328ft) @4K on shielded Kramer HDBaseT cable (or equivalent)  
**48V DC Power**



# KRAMER

## TECHNICAL SPECIFICATIONS

---

INPUT/OUTPUT:	1 HDBaseT/LAN + PoE on an RJ-45 connector, 1 HDBaseT/LAN on an RJ-45 connector
OPERATION BANDWIDTH:	Up to 10.2Gbps (3.4Gbps per data channel)
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI, HDCP
INDICATOR LEDES:	ON, PoE STATUS
POWER SOURCE:	48V DC, 630mA (device plus remote power sink)
POWER PROVISION:	Up to 13W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
COOLING:	Convection, vents
ENCLOSURE TYPE:	Aluminum
RACK MOUNT:	With optional adapter
FURNITURE MOUNT:	With included rubber feet
VIBRATION:	ISTA 1A in carton (International Safe Transit Association)
SAFETY REGULATORY COMPLIANCE:	CE, c-UL, UL
EMI/EMC REGULATORY COMPLIANCE:	CE, C-tick, FCC Class A, ICES, KCC, VCCI
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
INCLUDED ACCESSORIES:	Power supply
WARRANTY:	7 years parts and labor
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
Product Weight	0.2kg (0.4lbs) approx
Shipping Dimensions	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H
Shipping Weight	0.7kg (1.5lbs) approx

