



VGA-IN2-F16

2-Channel VGA Input Card

| Kramer Core



VGA-IN2-F16 is a two-channel VGA input card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The VGA-IN2-F16 inputs two VGA signals into the chassis

FEATURES

- Max bandwidth - 450MHz
- Auto or User-Defined Resolution Detection & Phase Mode
- Adjustable Brightness & Contrast



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------------|--|
| PORTS: | 2 VGA on 15-pin HD connectors |
| BANDWIDTH: | 450MHz |
| MAXIMUM RANGE: | 10m (32ft) |
| POWER CONSUMPTION: | 5.5W |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| SAFETY REGULATORY COMPLIANCE: | CE |
| ENVIRONMENTAL REGULATORY COMPLIANCE: | Complies with appropriate requirements of RoHs and WEEE |
| Product Dimensions | 19.00cm x 13.00cm x 2.00cm (7.48" x 5.12" x 0.79") W, D, H |
| Product Weight | 0.1kg (0.3lbs) approx |
| Shipping Dimensions | 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H |
| Shipping Weight | 0.3kg (0.6lbs) approx |