



VGAA-OUT4-F32

4-Channel VGA with Analog Audio Output
Card

| Kramer Core



VGAA-OUT4-F32 is a four-channel VGA with analog audio output card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The VGAA-OUT4-F32 outputs four VGA with analog audio signals from the chassis. Audio output is accessed by connecting the supplied Kramer VGA with audio cables to each VGA port

FEATURES

- Max. Bandwidth - 450MHz
- HDTV Compatible
- Analog Audio Over Breakaway Connector



KRAMER

TECHNICAL SPECIFICATIONS

OUTPUTS	4 VGA on 15-pin HD connectors, 4 unbalanced analog audio on 3.5mm mini jack connectors (accessible via C GF/GMAF-30 cables)
BANDWIDTH:	450MHz
MAXIMUM RANGE:	10m (32ft)
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
Power Consumption	10W
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
INCLUDED ACCESSORIES:	4 C-GF/GMAF-30 cables